

Electrical Characteristics BL2610 Series

Part Number	Inductance (μ H)	Test Frequency (Khz)	DC Resistance (Ω) Max.	Rated DC Current (A) Max.
BL2610-1R0M	1.0	100	0.065	3.84
BL2610-1R5M	1.5	100	0.068	3.00
BL2610-2R2M	2.2	100	0.090	2.50
BL2610-3R3M	3.3	100	0.110	1.90
BL2610-4R7M	4.7	100	0.130	1.70
BL2610-6R8M	6.8	100	0.150	1.30
BL2610-100M	10	100	0.210	1.20
BL2610-150M	15	100	0.270	0.95
BL2610-220M	22	100	0.380	0.80
BL2610-330M	33	100	0.560	0.65
BL2610-470M	47	100	0.740	0.56
BL2610-680M	68	100	1.000	0.41
BL2610-101M	100	100	2.100	0.34
BL2610-151M	150	100	3.000	0.28
BL2610-221M	220	100	3.600	0.23
BL2610-331M	330	100	4.800	0.18
BL2610-471M	470	100	8.000	0.17
BL2610-681M	680	100	10.500	0.13
BL2610-102M	1000	100	17.700	0.11

Note:

Rated DC Current: Inductance drops 10%(Max.) from its initial value, or temperature rise by 40°C (Ta=25°C), whichever is smaller.

Test equipment: Inductance is measured with WK3260A Meter or equivalent.

Operating temperature range: -25°C to +85°C